



GUANGDONG LEVA PACKAGING EQUIPMENT CO., LTD

Add: No. 3, Gongye South Road, Mingzhu Industrial Park, Conghua District, Guangzhou City, Guangdong Province, China. 510900

TEL: 020-37510321 **WEB:** www.levapack.cn **EMAIL:** info@levapack.com

Equipment name: 8-head liquid filling machine

Model: LPE-CLB08



(The equipment is updated irregularly, and the appearance of the equipment is subject to the final production.)

Product features:

1. Stainless steel gear pump is used for filling, which is convenient for cleaning and changing tubes.
2. The glass one-way valve prevents dripping to ensure that the filling process reduces dripping.
3. The linear bottle feeding design has a large packaging material compatibility and is suitable for a variety of bottle varieties. It is simple and fast to change the packaging material for filling.
4. Automatic induction of bottles in and out, the number of filling bottles can be set, and a single discharge head can be flexibly selected/disabled.
5. The machine is small and can be used in different occasions.
6. It is widely used in food, medicine, daily chemical and other industries; such as liquor, sauce and vinegar, milk, beverages, mineral water, liquid medicine, edible oil and chemical raw materials and other liquids without particles and impurities.

Technical parameters:

1. Filling speed: 0-80 bottles/minute (depending on the material and filling volume)
2. Power supply: 220V 50-60Hz
3. Machine power: 2.2KW 4 heads (1.2KW) 6 heads (1.5KW)
4. Filling range: 5ml-infinite (adjustable, time controlled)
5. Filling method: cylinder lifting, can dive into the bottle for filling, can be disabled
6. Pump head pressure resistance: 16-20Bar (self-priming)
7. Maximum flow: single head 5L/minute (based on water medium, the maximum flow is about 90ml/second)
8. Filling accuracy: $0.5\% \leq$ (depending on the material)
9. Applicable bottle height range (mm): 30-250MM
10. Applicable bottle diameter range (mm): 15-100mm
11. Working air pressure: 0.4-0.6MPa
12. Equipment size: length 2500*width 860*height 1550mm (equipment size varies with different filling heads)

Configuration table (standard configuration, actual production will be partially adjusted, subject to final production)

Standard configuration is all domestic accessories, the following configuration prices are different.

No.	Part name	Brand	Origin	Picture
1	Touch screen	Kunlun	China	
2	Photoelectric sensor	AUTONIX	Korea	
3	Pneumatic component	AIRTAC	Taiwan	
4	Step motor	LINENG	China	